






# P803 P803C

Lima Rotativa – Cilíndrica com Corte no Topo. Soldada acima de 6.00 mm.

P803 P803C	P1.1	P1.2	P1.3	P2.1	P2.2	P2.3	P3.1	P3.2	P3.3	P4.1	P4.2	P4.3	M1.1	M1.2	M2.1	M2.2	M2.3	
	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
	M3.1	M3.2	M3.3	M4.1	M4.2	K1.1	K1.2	K1.3	K2.1	K2.2	K2.3	K3.1	K3.2	K3.3	K4.1	K4.2	K4.3	
	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
	K4.4	K4.5	K5.1	K5.2	K5.3	N3.1	N3.2	N3.3	S1.1	S1.2	S1.3	S2.1	S2.2	S3.1	S3.2	S4.1	S4.2	
	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
	H1.1	H2.1	H2.2	H3.1	H3.2	H4.1	H4.2											
	■	■	■	■	■	■	■											

P803	HM	B				DC		 40 P880	 40 P890
P803C	HM	B			TiAlN	DC		 40 P880	

 DORMER



P803	P803C
	
3.00 – 16.00	3.00 – 12.70

DC	DCON MS h7	APMX	OAL	P803	P803C
[mm]	[mm]	[mm]	[mm]		
3.00	3	14	38	P8033.0X3.0 <sup>1)</sup>	P803C3.0X3.0 <sup>1)</sup>
6.30	3	12.7	45	P8036.3X3.0	
6.00	6	18	50	P8036.0X6.0 <sup>1)</sup>	P803C6.0X6.0 <sup>1)</sup>
8.00	6	19	64	P8038.0X6.0	P803C8.0X6.0
9.60	6	19	64	P8039.6X6.0	P803C9.6X6.0
12.70	6	25	70	P80312.7X6.0	P803C12.7X6.0
16.00	6	25	70	P80316.0X6.0	

<sup>1)</sup> DCON MS tolerância h6