

P809

Lima Rotativa – Oval. Soldada acima de 6.00mm.

P809	P1.1	P1.2	P1.3	P2.1	P2.2	P2.3	P3.1	P3.2	P3.3	P4.1	P4.2	P4.3	M1.1	M1.2	M2.1	M2.2	M2.3
	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
	M3.1	M3.2	M3.3	M4.1	M4.2	K1.1	K1.2	K1.3	K2.1	K2.2	K2.3	K3.1	K3.2	K3.3	K4.1	K4.2	K4.3
	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
	K4.4	K4.5	K5.1	K5.2	K5.3	N3.1	N3.2	N3.3	S1.1	S1.2	S1.3	S2.1	S2.2	S3.1	S3.2	S4.1	S4.2
	■	■	■	■	■	■	■	□	■	■	■	■	■	■	■	■	■
	H1.1	H2.1	H2.2	H3.1	H3.2	H4.1	H4.2										
	■	■	■	■	■	■	■										

P809

HM

E



DC

DORMER



DORMER



P809



3.00 – 16.00

DC	DCON MS h7	APMX	OAL	P809
[mm]	[mm]	[mm]	[mm]	
3.00	3	6	38	P8093.0X3.0 ¹⁾
6.30	3	9.5	42	P8096.3X3.0
6.00	6	10	50	P8096.0X6.0 ¹⁾
8.00	6	15	60	P8098.0X6.0
9.60	6	16	60	P8099.6X6.0
12.70	6	22	67	P80912.7X6.0
16.00	6	25	70	P80916.0X6.0

¹⁾ DCON MS tolerância h6